

# ? CentOS 7 ?????? OxOOL

- [CentOS 7 SELinux \(disabled\) 配置](#) CentOS 7 配置 OxOOL  
SELinux 配置 root

- [配置 OxOOL](#)

```
sudo systemctl stop oxool
sudo systemctl disable oxool
```

- [配置 OxOOL 环境](#)

```
sudo yum install epel-release -y
sudo yum update -y
sudo yum install git yum-utils libpcap libcap-devel poco-devel ccache python36-polib python36-lxml -y
sudo yum install libtool gcc-c++ fontconfig-devel cppunit-devel pam-devel rpm-build -y
```

- [配置 Node.js](#)

```
curl -fsSL https://rpm.nodesource.com/setup_16.x | sudo bash -
sudo yum install nodejs -y
```

- [配置 OxOOL 仓库 clone](#)

```
git clone https://github.com/OSSII/oxool-community.git
```

- [配置 OxOOL 编译](#)

```
cd oxool-community
./autogen.sh
./configure
make dist
rpmbuild -tb oxool-x.x.x.tar.gz #配置仓库clone 配置仓库 oxool-3.2.11.tar.gz 配置仓库
oxool-x.x.x.tar.gz 配置仓库
```

- [配置 rpm 仓库](#)

~/rpmbuild/RPMS/x86\_64



---

Revision #25

Created 2020-05-18 07:53:26 UTC by kevin

Updated 2022-12-14 03:27:12 UTC by Jeff Huang